

Package ‘LBE’

May 14, 2024

Type Package

Title Estimation of the false discovery rate.

Version 1.72.0

Date 2007-01-10

Author Cyril Dalmasso

Maintainer Cyril Dalmasso <dalmasso@vjf.inserm.fr>

Description LBE is an efficient procedure for estimating the proportion of true null hypotheses, the false discovery rate (and so the q-values) in the framework of estimating procedures based on the marginal distribution of the p-values without assumption for the alternative hypothesis.

Depends stats

Imports graphics, grDevices, methods, stats, utils

License GPL-2

Suggests qvalue

biocViews MultipleComparison

git_url <https://git.bioconductor.org/packages/LBE>

git_branch RELEASE_3_19

git_last_commit 8d6f9c4

git_last_commit_date 2024-04-30

Repository Bioconductor 3.19

Date/Publication 2024-05-14

Contents

LBE-package	2
golub.pval	3
hedenfalk.pval	3
LBE	4
LBEa	6

LBEplot	7
LBEsummary	8
LBEwrite	9

Index	11
--------------	-----------

LBE-package	<i>Estimation of the proportion of true null hypotheses, the false discovery rate and the q-values.</i>
-------------	---

Description

The package LBE allows estimating the proportion of true null hypotheses and the false discovery rate.

Details

Package: LBE
 Type: Package
 Version: 1.13.2
 Date: 2007-1-10
 License: GPL-2

Author(s)

Cyril Dalmasso Maintainer: Cyril Dalmasso <dalmasso@vjf.inserm.fr>

References

Dalmasso C, Broet P, Moreau T (2005): A simple procedure for estimating the false discovery rate. *Bioinformatics*, 21: 660 - 668.

Storey JD and Tibshirani R. (2003). Statistical significance for genome-wide studies. *Proc Natl Acad Sci*, 100, 9440-9445.

See Also

LBE is an alternative method to the one proposed by Storey and Tibshirani (2003) for estimating the q-values, this latter method being implemented in the package [qvalue](#).

golub.pval	<i>p-values corresponding to the gene expression data from Golub et al. (1999).</i>
------------	---

Description

The aim of the study of Golub et al. *Golub* was to identify differentially expressed genes between acute myeloid leukemia (AML) and acute lymphoblastic leukemia (ALL). The samples were assayed using Affymetrix Hgu6800 chips and the data on the expression of 7129 genes are available in the Bioconductor package `golubEsets`. The p-values provided here were calculated from a two-sample t-test analysis. The variance-stabilizing method included in the `vs` package was applied for normalizing the data.

Usage

```
data(golub.pval)
```

Format

The format is: num [1:3051] 0.0170 0.2552 0.9130 0.7867 0.2431 ...

References

Golub TR, Slonim DK, Tamayo P, Huard C, Gaasenbeek M, Mesirov JP, Coller H, Loh ML, Downing JR, Caligiuri MA, Bloomfield CD, Lander ES (1999). Molecular classification of cancer: class discovery and class prediction by gene expression monitoring. *Science*, 15, 286(5439), 531-7.

hedenfalk.pval	<i>p-values corresponding to the gene expression data from Hedenfalk et al. (2001).</i>
----------------	---

Description

The aim of the study of Hedenfalk et al. (2001) was to examine breast-cancer tissues from patients with BRCA1-BRCA2 related cancer and cases of sporadic breast cancer to determine global gene expression patterns in the different classes of tumours. Here, we focus on the comparison of BRCA1 and BRCA2. The p-values provided here are the same as those provided with the package `qvalue`. They were obtained from a two-sample t-test analysis on a subset of 3,170 genes, as described in Storey and Tibshirani (2003).

Usage

```
data(hedenfalk.pval)
```

Format

The format is: num [1:3170] 0.0121 0.0750 0.9949 0.0418 0.8458 ...

References

Hedenfalk I, Duggan D, Chen Y, Radmacher M, Bittner M, Simon R, Meltzer P, Guterson B, Esteller M, Kallioniemi OP et al. (2001) Gene-expression profiles in hereditary breast cancer. *N Engl J Med*, 22, 539-548.

Storey JD and Tibshirani R. (2003). Statistical significance for genome-wide studies. *Proc Natl Acad Sci*, 100, 9440-9445.

LBE

Estimation of the false discovery rate.

Description

LBE is an efficient procedure for estimating the proportion of true null hypotheses, the false discovery rate and the q-values.

Usage

`LBE(pval, a = NA, l = 0.05, ci.level = 0.95, qvalues = TRUE, plot.type = "main", FDR.level = 0.05, n.significant = NA)`

Arguments

<code>pval</code>	Numerical vector of p-values (only necessary input).
<code>a</code>	Real value used in $[-\ln(1 - pi)]^a$ (see details). If <code>a == NA</code> (default), then the value of <code>a</code> is automatically calculated as the greatest value such that the upper bound of the asymptotic standard deviation of the estimator of π_0 is smaller than the threshold <code>l</code> . If <code>a >= 1</code> , the value of <code>a</code> is used in $[-\ln(1 - pi)]^a$ (see details). If <code>a < 1</code> , the identity function is used for transforming the p-values.
<code>l</code>	Threshold for the upper bound of the asymptotic standard deviation (only used if <code>a == NA</code>).
<code>ci.level</code>	Level for the confidence interval of π_0 .
<code>qvalues</code>	Logical value for estimating the qvalues and the FDR. If <code>qvalues = FALSE</code> , only the proportion π_0 of true null hypotheses is estimated.
<code>plot.type</code>	If <code>plot.type = "none"</code> , no graphic is displayed. If <code>plot.type = "main"</code> , the estimated q-values versus the p-values are plotted together with the histogram of the p-values. If <code>plot.type = "multiple"</code> , several graphics are displayed: 1. The histogram of the p-values 2. The estimated q-values versus the p-values 3. The number of significant tests versus each qvalue cutoff 4. The number of expected false positives versus the number of significant tests.
<code>FDR.level</code>	Level at which to control the FDR (only used if <code>n.significant == NA</code>).
<code>n.significant</code>	If specified, the FDR is estimated for the rejection region defined by the "n.significant" smallest p-values.

Details

The procedure LBE is based on the expectation of a particular transformation of the p-values leading to a straightforward estimation of the key quantity π_0 that is the proportion of true null hypotheses:

$$\pi_0(a) = \{(1/m) * \sum_{i=1}^m [-\ln(1 - p_i)]^a\} / \Gamma(a + 1), \text{ where } a \text{ belongs to the interval } [1; \text{inf}).$$

Value

A list containing:

call	Function call.
FDR	Level at which to control the FDR (if n.significant == NA) or estimated FDR (if n.significant != NA).
π_0	Estimated value of π_0 , the proportion of true null hypotheses.
$\pi_0.ci$	Confidence interval for π_0 .
ci.level	Level for the confidence interval of π_0 .
a	Value used in $[-\ln(1 - p_i)]^a$ (see details).
l	Upper bound of the asymptotic standard deviation for π_0 .
qvalues	Vector of the estimated q-values.
pvalues	Vector of the original p-values.
significant	Indicator of whether the null hypothesis is rejected.
n.significant	Number of rejected null hypotheses.

Note

LBE is an alternative method to the one proposed by Storey and Tibshirani (2003) for estimating the q-values, this latter method being implemented in the package qvalue.

Author(s)

Cyril Dalmasso

References

Dalmasso C, Broet P, Moreau T (2005). A simple procedure for estimating the false discovery rate. *Bioinformatics*. *Bioinformatics*, 21: 660 - 668.

Storey JD and Tibshirani R. (2003). Statistical significance for genome-wide studies. *Proc Natl Acad Sci*, 100, 9440-9445.

See Also

[LBEplot](#), [LBEsummary](#), [LBEwrite](#), [LBEa](#)

Examples

```
## start
data(hedenfalk.pval)
res=LBE(hedenfalk.pval)
data(golub.pval)
res=LBE(golub.pval)
## end
```

LBEa

*Optimal setting for the parameter a***Description**

The LBEa function is called by the main function LBE for choosing the greatest value of a such that the upper bound of the asymptotic standard deviation is less than a threshold l. A plot illustrating the relation between a and l for a fixed number of tested hypotheses can also be displayed.

Usage

```
LBEa(m, l = 0.05, fig = TRUE, a.rng = NA)
```

Arguments

m	Total number of tested hypotheses.
l	Threshold for the upper bound of the asymptotic standard deviation (default value is 0.05).
fig	Logical value for plotting the standard deviation versus a.
a.rng	Range of values of a to consider. If a.rng == NA, a.rng is set such that the standard deviation is less than 0.5.

Details

The procedure LBE is based on the expectation of a particular transformation of the p-values leading to a straightforward estimation of the key quantity π_0 that is the proportion of true null hypotheses:

$$\pi_0(a) = (1/m) * \sum_{i=1}^m [-\ln(1 - p_i)]^a / \Gamma(a + 1)$$

where a belongs to the interval $[1; \infty)$. As there is a balance between bias (decreasing as a increase) and variance (increasing as a increase), for a specified number m of tested hypotheses, we have proposed to choose the greatest value of a such that the upper bound of the asymptotic standard deviation of the estimator of π_0 is smaller than the threshold l. The function LBEa allows to plot the standard deviation versus a in order to help for the choice of the threshold l (for a specific number m of tested hypotheses).

Value

a Greatest value of a such that the the upper bound of the asymptotic standard deviation of the estimator of π_0 is smaller than the threshold l .

Author(s)

Cyril Dalmasso

References

Dalmasso C, Broet P, Moreau T (2005). A simple procedure for estimating the false discovery rate. *Bioinformatics*. *Bioinformatics*, 21: 660 - 668.

See Also

[LBE](#), [LBEplot](#), [LBEsummary](#), [LBEwrite](#)

Examples

```
## start
data(hedenfalk.pval)
m <- length(hedenfalk.pval)
LBEa(m,l = 0.05)
## end
```

LBEplot

Graphical display of LBE objects.

Description

Graphical display of LBE objects.

Usage

```
LBEplot(LBEobj, rng = c(0, 0.1), plot.type = c("multiple", "main"), legend = TRUE)
```

Arguments

LBEobj	LBE object.
rng	Range of q-values to consider.
plot.type	If plot.type == "main", The estimated q-values versus the p-values are plotted together with the histogram of the p-values. If plot.type == "multiple" (default value), several graphics are displayed.
legend	Logical value for displaying the legend on the plot (when plot.type == "main").

Details

If `plot.type == "multiple"`, the following graphics are displayed: 1. The histogram of the p-values. 2. The estimated q-values versus the p-values. 3. The number of significant tests versus each qvalue cutoff. 4. The number of expected false positives versus the number of significant tests.

Note

The function `LBEplot` is analogous to the function `qplot` from the package `qvalue`.

Author(s)

Cyril Dalmasso

See Also

[LBE](#), [LBEsummary](#), [LBEwrite](#), [LBEa](#)

Examples

```
## start
data(hedenfalk.pval)
res=LBE(hedenfalk.pval,plot.type="none")
LBEplot(res)
LBEplot(res,plot.type="main")
LBEplot(res,plot.type="main",legend=FALSE)
## end
```

LBEsummary

Display LBE object

Description

Display summary information for an LBE object.

Usage

```
LBEsummary(LBEobj, cuts = c(1e-04, 0.001, 0.01, 0.025, 0.05, 0.1, 1), digits = getOption("digits"), ...)
```

Arguments

<code>LBEobj</code>	LBE object.
<code>cuts</code>	Vector of significance value to use for table.
<code>digits</code>	Significant digits to display.
<code>...</code>	Any other arguments.

Details

LBEsummary shows the original call, estimated proportion of true null hypotheses, confidence interval for the proportion of true null hypotheses and a table comparing the number of significant calls for the p-values and for the estimated q-values using a set of cutoffs given by the argument cuts.

Value

Invisibly returns the original object.

Note

The function LBEsummary is analogous to the function qsummary from the package qvalue.

Author(s)

Cyril Dalmasso

See Also

[LBE](#), [LBEplot](#), [LBEwrite](#), [LBEa](#)

Examples

```
## start
data(hedenfalk.pval)
res<-LBE(hedenfalk.pval)
print(res)
LBEsummary(res)
## end
```

LBEwrite

Write the results of an LBE object to a file.

Description

Write the results of an LBE object to a file.

Usage

```
LBEwrite(LBEobj, filename = "LBE-results.txt")
```

Arguments

LBEobj	LBE object
filename	Output filename (optional)

Details

The output file lists the estimate of π_0 , which is the proportion of true null hypotheses. It also lists each p-value and corresponding q-value, one per line. If an FDR significance level was specified in the call to `qvalue`, the significance level is printed below the estimate of π_0 , and an indicator of significance is included as a third column for each p-value and q-value.

Note

The function `LBEwrite` is analogous to the function `qwrite` from the package `qvalue`.

Author(s)

Cyril Dalmasso

See Also

[LBE](#), [LBEplot](#), [LBEsummary](#), [LBEa](#)

Examples

```
## start
data(hedenfalk.pval)
res<-LBE(hedenfalk.pval)
LBEwrite(res,filename="myresults.txt")
## end
```

Index

- * **datasets**
 - golub.pval, 3
 - hedenfalk.pval, 3
- * **htest**
 - LBE, 4
 - LBEplot, 7
 - LBEsummary, 8
 - LBEwrite, 9
- * **misc**
 - LBEa, 6
- * **package**
 - LBE-package, 2

golub.pval, 3

hedenfalk.pval, 3

LBE, 4, 7–10

LBE-package, 2

LBEa, 5, 6, 8–10

LBEplot, 5, 7, 7, 9, 10

LBEsummary, 5, 7, 8, 8, 10

LBEwrite, 5, 7–9, 9

qvalue, 2