

Package ‘muscle’

November 13, 2024

Type Package

Title Multiple Sequence Alignment with MUSCLE

Version 3.48.0

Date 2012-10-05

Author Algorithm by Robert C. Edgar. R port by Alex T. Kalinka.

Maintainer Alex T. Kalinka <alex.t.kalinka@gmail.com>

Description MUSCLE performs multiple sequence alignments of nucleotide or amino acid sequences.

biocViews MultipleSequenceAlignment, Alignment, Sequencing, Genetics, SequenceMatching, DataImport

Depends Biostrings

License Unlimited

URL <http://www.drive5.com/muscle/>

LazyLoad yes

LazyData yes

NeedsCompilation yes

git_url <https://git.bioconductor.org/packages/muscle>

git_branch RELEASE_3_20

git_last_commit 7978165

git_last_commit_date 2024-10-29

Repository Bioconductor 3.20

Date/Publication 2024-11-12

Contents

| | |
|--------------------------|---|
| muscle-package | 2 |
| muscle | 2 |
| umax | 3 |

| | |
|--------------|----------|
| Index | 5 |
|--------------|----------|

muscle-package *Multiple Sequence Alignment*

Description

MUSCLE performs multiple sequence alignments of nucleotide and amino acid sequences.

Details

Details about the algorithm can be found on the MUSCLE website:

<http://www.drive5.com/muscle/>

Author(s)

Algorithm: Robert C. Edgar

R port: Alex T. Kalinka <alex.t.kalinka@gmail.com>

References

Edgar, R.C. (2004) MUSCLE: multiple sequence alignment with high accuracy and high throughput. *Nucleic Acids Res* **32**, 1792-1797.

See Also

[muscle](#), [umax](#)

Examples

```
## Align sequences in an XStringSet object.  
## Not run:  
aln <- muscle(stringset = umax)  
  
## End(Not run)
```

muscle *Multiple Sequence Alignment*

Description

MUSCLE performs multiple sequence alignments of nucleotide or amino acid sequences.

Usage

```
muscle(stringset, quiet = FALSE, ...)
```

Arguments

| | |
|-----------|--|
| stringset | An object of class <i>XStringSet</i> : <i>DNAStrngSet</i> , <i>RNAStrngSet</i> , or <i>AAStringSet</i> . |
| quiet | Logical, whether to prevent printing of the progress of the algorithm to the screen. Defaults to FALSE. |
| ... | Arguments (options and flags) for the MUSCLE algorithm (see Details). |

Details

Arguments for the MUSCLE algorithm are either options or flags. Options take a variety of values, but flags are always logicals (TRUE or FALSE). All options and flags are explained in detail on the MUSCLE website: http://www.drive5.com/muscle/muscle_userguide3.8.html

Value

Output is an object of class `MultipleAlignment`: `DNAMultipleAlignment`, `RNAMultipleAlignment`, or `AAMultipleAlignment`.

Note

For further details see the MUSCLE website: <http://www.drive5.com/muscle/>

Author(s)

Algorithm by Robert C. Edgar. Ported into R by Alex T. Kalinka <alex.t.kalinka@gmail.com>

References

Edgar, R.C. (2004) MUSCLE: multiple sequence alignment with high accuracy and high throughput. *Nucleic Acids Res* **32**, 1792-1797.

See Also

[umax](#)

Examples

```
## Align sequences in an XStringSet object.
aln <- muscle(stringset = umax)

## Switch on the diags flag.
aln <- muscle(stringset = umax, diags = TRUE)
```

umax

Unaligned MAX sequences

Description

Unaligned DNA sequences of the MAX gene for 31 mammalian species.

Usage

```
umax
```

Format

An object of class `DNAStrngSet`.

Value

An object of class [DNAStrngSet](#).

Source

<http://www.ensembl.org/index.html>

References

Wagner, AJ et al. (1992) Expression, regulation, and chromosomal localization of the Max gene. *Proc Natl Acad Sci USA* **89**: 3111-3115.

Index

* datasets

umax, [3](#)

AAMultipleAlignment, [3](#)

AAStringSet, [2](#)

DNAMultipleAlignment, [3](#)

DNAStrngSet, [2-4](#)

MultipleAlignment, [3](#)

muscle, [2, 2](#)

muscle-package, [2](#)

RNAMultipleAlignment, [3](#)

RNAStrngSet, [2](#)

umax, [2, 3, 3](#)

XStringSet, [2](#)